



PORTÝR tractor container carriers

PORTÝR tractor container carriers

PORTÝR tractor container carriers are primarily intended for the transport and handling of various types of container bodies. PORTÝR carriers are prepared in every respect for the long-term load in agricultural, building and municipal operations.

PORTÝR container carriers with single axle

Technical parameters	PORTÝR 3.2	PORTÝR 4.3	PORTÝR 7.5	PORTÝR 8.6	PORTÝR 9.7	PORTÝR 13.10
Number of axles (pcs)	1	1	1	1	1	1
Maximum total allowable weight (kg)	3 200	4 200	7 000	8 000	9 000	13 000
Mechanism capacity (kg)	3 000	3 000	5 000	6 000	7 000	8 000
Optimum container length (mm)	2 800	2 800	3 900	4 300	4 300	4 600
Min/max container length (mm)	2 800	2 800	3 900	3 600 - 4 300	3 600 - 4 300	3 900 - 4 600
Max. total length (mm)	3 700	3 700	4 980	5 513	5 575	6 131
Total width (mm)	1 770	1 770	2 500	2 500	2 500	2 500
Speed limit (km/hour)	40	40	40	40	40	40

PORTÝR container carriers with two axles

Technical parameters	PORTÝR 12.9	PORTÝR 14.10	PORTÝR 19.12	PORTÝR 20.14	PORTÝR 22.16
Number of axles (pcs)	2	2	2	2	2
Maximum total allowable weight (kg)	12 000	14 000	19 000	20 000	21 000 - 22 000
Mechanism capacity (kg)	8 000	10 000	12 000	14 000	16 000
Optimum container length (mm)	4 600	5 100	5 300	5 700	6 300
Min/max container length (mm)	3 900 - 4 600	4 300 - 5 100	4 500 - 5 300	4 800 - 5 700	5 300 - 6 300
Max. total length (mm)	6 131	6 530	6 635	7 076	7 677
Total width (mm)	2 500	2 500	2 550	2 550	2 550
Speed limit (km/hour)	40	40	40/60	40/60	40/60

PORTÝR container carriers with three axles

Technical parameters	PORTÝR 27.20
Number of axles (pcs)	3
Maximum total allowable weight (kg)	27 000
Mechanism capacity (kg)	20 000
Optimum container length (mm)	6 800
Min/max container length (mm)	5 800 - 6 800
Max. total length (mm)	8 640
Total width (mm)	2 550
Speed limit (km/hour)	40/60

